

Water Infiltration Test

*Do you need to have a product tested in the development or prototype stage?
Do you need qualification or pre-certification tests done?
Our professionals are here to help!*

TYPES OF TESTS

- Rain
- Wind driven rain
- Drip
- Mist
- Water spray (hosedown)
- Immersion
- Water tightness

ACCORDING TO STANDARDS

- BELLCORE TA-NWT-000487
- CAN/ULC S303
- CAN/CSA C22.2 No. 94
- IEC 68-2-18
- EN 60529 (IEC 529)
- MIL-STD 108E
- MIL-STD-810E
- MIL-STD-2039
- NEMA 250
- UL 50
- UL 497



CRIQ

CENTRE DE RECHERCHE
INDUSTRIELLE DU QUÉBEC

FIELDS OF APPLICATION

Equipments and enclosures for electrical, electronic and telecommunication equipments, construction materials, etc.

EQUIPMENTS

Nozzles
Reservoirs
Oscillating tubes
Shower
Hose
Axial blower

TESTING PARAMETERS

Wind pressure:	0-600 kPa
Wind speed:	Up to 70 mph (31 m/s)
Diameter at the blower exit:	32 in (81 cm)
Water pressure:	Up to 100 psi
Water flow:	Up to 60 gpm

INFORMATION

For more information, contact our customer service at :

(514) 383-3210 or 1 800 667-4570, ext. 3210.

or visit our web site : www.criq.qc.ca

CRIQ is certified ISO 9001

8475, avenue Christophe-Colomb, Montréal (Québec) Canada H2M 2N9

(1999-10)